

Normally Open WRAS Solenoid Valves

Pilot-Operated 230v Normally OPEN Solenoid Valves



- We recommend you mount coil upright
- It is recommended that you fit strainers to protect the valves from debris
- Optional 12vDC or 24v available on request
- Optional magnetic valve opener. Allows you to close valve without power
- Voltage $\pm 10\%$. Continuous Duty 100 %



Pilot Operated Solenoid Valves

Order Codes:

1/2"	230v HP N-OPEN Solenoid Valve
3/4"	230v HP N-OPEN Solenoid Valve
1"	230v HP N-OPEN Solenoid Valve
1 1/4"	230v HP N-OPEN Solenoid Valve
1 1/2"	230v HP N-OPEN Solenoid Valve
2"	230v HP N-OPEN Solenoid Valve

NOOPEN = Normally open

HP = Rated up to 10 bar.

1/2", 3/4" and 1" require 0.35 bar minimum pressure differential to operate

1 1/4", 1 1/2" and 2" require 0.5 bar minimum pressure differential to operate

Temperature up to 80°C

Power Absorption:

Pilot Operated HP Valves

For valve sizes 1/2", 3/4" & 1"

Inrush	Holding	DC
11.7 va	10 va	5.5W

For valve sizes 1 1/4", 1 1/2" & 2"

Inrush	Holding	DC
28 va	20 va	9W



ROBERT PEARSON & COMPANY LTD

Post Office House, Post Office Lane
Stockton, Warminster
Wiltshire BA12 0SE

Telephone: (01985) 850954

Facsimile: (01985) 850112

E-Mail: sales@robertpearson.co.uk

Website: www.robertpearson.co.uk