THF-M & THF-B Timed Hygiene Flush Kit

No PIR. Timer allows you to set from 1 flush per hour up to 1 flush per 12 hour period.



Order Codes:

THF-M Mains powered kit **THF-B** Battery powered kit 120mm × 100mm × 45mm

Each kit c/w:

WRAS approved 15mm solenoid valve
Control module c/w adjustable time controls
Battery powered units come with long life battery pack
Mains powered units come with separate transformer unit (to be wired to 3A fused spur)



Solenoid Valve for controlled "reduced splash" filling of urinal cistern For mains & battery powered kits

Standard 15mm (2mm Orifice) Valve to fit on an inlet pipe to a single cistern as standard

You will need to provide length of 2 core cable from valve to PIR sensor


ORDER CODE 15mm 6vDC (2mm Orifice) Valve

TECHNICAL DATA

Material Brass
O-ring/washers NBR (Nitrile)
Pressure rating 0 Bar – 10 Bar max.

Orifice2mm

Connection 15mm compression





Not using a cistern? Controlling more than one cistern?

If you are not using a cistern or want $1 \times \text{valve}$ to control more than one cistern, please call to discuss options for a larger sized orifice solenoid valve.



ROBERT PEARSON & COMPANY LTD

Post Office House, Post Office Lane Stockton, Warminster Wiltshire BA12 OSE

Telephone: (01985) 850954 Facsimile: (01985) 850112 E-Mail: sales@robertpearson.co.uk Website: www.robertpearson.co.uk