AV SENSOR (or TOUCHPAD SWITCH) OPERATED WC FLUSHVALVE for our HIGH SECURITY WC PANS

Vandal Resistant and Anti-Ligature: All sensors (and touchpad switches) are anti-ligature. **Reduce Maintenance:** No mechanical handles or linkages to break. Helps reduce blockages.

Remote Anti Vandal Sensor (or Touchpad Switch) Kits for High Security WC Pan

Each Kit comes with: 1 x pre-wired Flushing Valve, 1 x Control Box and 1 x pre-wired Sensor (or Touchpad Switch). Please confirm total wall thickness as you may require optional extension threads. Pre-wired with 3m cable as standard. Longer cable lengths available. If required, please contact us.

No Touch AV Sensor Kits

To operate put hand within 50mm of the AV sensor

Mains Powered Order Code: WCFV-io-AV (2")

Battery Powered Order Code: WCFV-B-AV (2")




Touchpad Switch Kits


Require a small push to make the contact

Mains Powered Order Code: WCFV-io-TPS (2")

Battery Powered Order Code: WCFV-B-TPS (2")








Mains WC Control Box

Electrical supply: 12v DC from integral transformer. Connected to 220–240 AC mains.

Control box dimensions: 120mm (w) x 185mm (h) x 75mm (d) **Control box weight:** 950g


Battery Control Box



Electrical supply: 9v DC from 6 x 'C'-cell battery pack. Amps: 0.14A (max.) Control box dimensions: 120mm (w) x 185mm (h) x 75mm (d) Control box weight: 1kg

Pre-wired Flushvalve (2")





2" base connection for compatibility with our flat bottomed cisterns c/w 2" flush pipe. Valve c/w internal overflow pipe.

Valve open time adjustable from 0.25–6.75 seconds per flush. 1 second = 1 litre *approx*. Once a flush has been activated there is a 30 second delay (approx.) before the next flush can work to prevent abuse of the system.



ROBERT PEARSON & COMPANY LTD

Post Office House, Post Office Lane Stockton, Warminster Wiltshire BA12 OSE

Telephone: (01985) 850954 Facsimile: (01985) 850112 E-Mail: sales@robertpearson.co.uk Website: www.robertpearson.co.uk